



SEC A-A

| REV.   | REVISIONS REC. |     |              | DATE              | REV.       | REVISIONS REC.      |             |                   | DATE |
|--|----------------|-----|--------------|-------------------|------------|---------------------|-------------|-------------------|------|
| A  |                |     |              |                   | C          |                     |             |                   |      |
| B  |                |     |              |                   | D          |                     |             |                   |      |
| DRAWN &<br>DRAFTED BY  |                | 陈圣元 | TOLERANCES   |                   | ANGLE:     | TITLE:              |             |                   |      |
| CHECKED &<br>APPROVED BY   |                |     | 0<L≤4 ±0.1   | PIN PITCH<br>±0.2 | ±1°        | BOBBIN EF25 (10PIN) |             |                   |      |
|  |                |     | 4<L≤16 ±0.2  |                   | UNIT:      | BOBBIN MATERIAL:    |             | UL REC.           |      |
|  |                | 李自雄 | 16<L≤63 ±0.3 |                   | MM         | PHENOLIC            |             | UL 94V-0          |      |
| SX 深圳市三湘源电子科技有限公司<br>SANXIANG ELECTRONICS FACTORY<br>TEL: 86-755-28981958 FAX: 86-755-28981066 |                |     |              |                   | SCALE:     | PIN MATERIAL:       |             | PIN TENSION LOAD: |      |
|  |                |     |              |                   | 1.5/1      | CP WIRE             |             | 1.5Kg             |      |
|  |                |     |              |                   | DATE:      |                     | DRAWING NO: |                   | REV. |
|  |                |     |              |                   | 2007.07.01 | SX-2506             |             | 0                 |      |