



SEC A-A

|                          |                |     |  |  |      |                  |  |                            |      |
|--------------------------|----------------|-----|--|--|------|------------------|--|----------------------------|------|
| REV.                     | REVISIONS REC. |     |  | DATE   | REV. | REVISIONS REC.   |  |                            | DATE |
| A                        |                |     |  |  | C    |                  |  |                            |      |
| B                        |                |     |  |  | D    |                  |  |                            |      |
| DRAWN &<br>DRAFTED BY    |                | 陈圣元 |  | TOLERANCES                                   |      | ANGLE: ± 1°      |  |                            |      |
| CHECKED &<br>APPROVED BY |                | 李自雄 |  | 0<L≤4 ± 0.1<br>4<L≤16 ± 0.2<br>16<L≤63 ± 0.3 |      | PIN PITCH ± 0.2  |  | TITLE: BOBBIN ER35 (16PIN) |      |
|                          |                |     |  |  |      | UNIT: MM         |  | BOBBIN MATERIAL: PHENOLIC  |      |
|                          |                |     |  |  |      |                  |  | UL REC. UL 94V-0           |      |
|                          |                |     |  |  |      | SCALE: 1.5/1     |  | PIN MATERIAL: CP WIRE      |      |
|                          |                |     |  |  |      |                  |  | PIN TENSION LOAD: 1.5Kg    |      |
|                          |                |     |  |  |      | DATE: 2007.07.01 |  | DRAWING NO: SX-3502        |      |
|                          |                |     |  |  |      |                  |  | REV. 0                     |      |